



Technical Specifications

Rated Pull	Rated Speed	Drum Capacity	Motor Power(hydraulic/electric)
kN	m/min	φmm*m	kW
5	≥12	φ15*100	2.2/3
10	≥12	φ15*100	4/5.5
15	≥12	φ15*100	6.3/7.5
20	≥12	φ15*100	8.5/11
30	≥12	φ28*140	11/15
40	≥12	φ18*150	15/22
50	≥12	φ36*170	15/22
70	≥12	φ36*170	22/30
80	≥12	φ26*200	22/45
100	≥12	φ28*200	30/45
125	≥12	φ28*200	45/55
130	≥9	φ28*200	30/45
150	≥9	φ30*250	30/45
180	≥9	φ30*250	45/55
200	≥9	φ40*250	60/75
250	≥9	φ44.5*250	60/75
280	≥9	φ45*250	75/90
300	≥9	φ50*250	75/90
350	≥9	φ52*50	90/110
400	≥9	φ56*250	90/120

450	≥9	φ56*250	90/135
500	≥9	φ58*250	120/150
550	≥9	φ57*250	120/165
600	≥9	φ64*250	132/180
700	≥9	φ56*250	160/210
800	≥9	φ58*250	200/240
900	≥9	φ60*250	200/270
1000	≥9	φ64*250	250/300

1. Driving type: manual type ,electric motor,hydraulic motor or diesel engine.

2. Waring head type :single or double.

3. Gypsy:single or double.

Note:Please inform us of the above three points when making an inquiry.

Above specifications only for reference, we can supply various winches according to your requirements.